

SPECIFICATIONS

2017 MULE™ 4010 4x4



POWER

Engine	4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled
Displacement	617cc
Bore x Stroke	76.0 x 68.0mm
Compression ratio	10.3:1
Maximum Torque	34.7 lb-ft @ 2500 rpm
Fuel System	DFI® w/ 34mm Mikuni throttle body
Ignition	Digital electronic
Transmission	Continuously Variable Transmission (CVT) with high and low range, forward, and reverse, 2WD/4WD
Final Drive	Shaft, selectable 4-wheel drive with dual-model differential
Alternator Output (max)	23 amp

CAPABILITY

Front Suspension / Wheel Travel	Independent, MacPherson strut/3.9 in
Rear Suspension / Wheel Travel	Semi-independent, De Dion axle with leaf springs and shocks/2.8 in
Front Tires	23x11-10 tubeless
Rear Tires	23x11-10 tubeless
Steering	Electric power assisted rack-and-pinion
Front Brakes	4-wheel hydraulic drums, sealed
Rear Brakes	4-wheel hydraulic drums, sealed
Ground Clearance	6.9 in
Fuel Capacity	6.3 gal
Turning Radius	11.2 ft
Cargo Bed Dimensions (LxWxH)	46.3 x 51.6 x 11.4 in
Cargo Bed Capacity	800 lb
Load Capacity	1330 lb
Seating Capacity	2
Towing Capacity	1200 lb
Lighting	(2) 35 W sealed-beam headlights, (2) 5/21 W tail/brake lights

DETAILS

Frame Type	Steel tube ladder type
Overall Length	116.7 in
Overall Width	62.0 in
Overall Height	75.8 in
Curb Weight	1432.6 lb**
Wheelbase	73.6 in
Instruments	Parking brake warning light, coolant temperature warning light, horn, 12V DC outlet
Color Choices	Timberline Green, Dark Royal Red
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI.COM

Kawasaki