

C-SLAB GRABBER

GUARDRAIL

FOR MORE INFO, PLEASE CALL
1.800.466.6385 OR VISIT GUARDIANFALL.COM

FEATURES & BENEFITS:

- DURABLE, POWDER-COATED STEEL
- COMPATIBLE WITH WIDE RANGE OF CONCRETE SLABS
- QUICK-ADJUST HANDLE
- EASY TO MOVE AS WORK PROGRESSES
- RESISTANT TO CORROSION AND DAMAGE

ALSO COMPATIBLE WITH CABLE AND SNAP-ON METAL RAILS.



OVERLAP 2X4'S OR 2X6'S

BACKUP SAFETY SYSTEM

ANTI-SLIP TAPE

IDEAL SOLUTION FOR INSTALLING GUARDRAILS ON CONCRETE DECKING

SPECS

STANDARDS:

OSHA 1910 & 1926 SUBPART M

MATERIALS:

POWDER-COATED STEEL AND GALVANIZED STEEL

MORE SPECS & REQUIREMENTS:

- C-SLAB GRABBER CAN BE ADJUSTED TO FIT CONCRETE BEAMS FROM 1½" TO 36" THICK.
- MAXIMUM PERMITTED SPACING BETWEEN C-SLAB GRABBERS IS 8'
- TOPRAILS MUST BE 42" (+/- 3") ABOVE THE WORK SURFACE OR, IF USED IN STILT WORK APPLICATIONS, 42" PLUS HEIGHT OF STILTS.

- TOEBOARDS ARE REQUIRED ON SURFACES WITH SLOPES MORE THAN 4/12 (VERTICAL/HORIZONTAL).
- TOEBOARDS MUST BE A MINIMUM 3½" FROM THEIR TOP EDGE TO THE WORK SURFACE, AND MUST NOT HAVE GREATER THAN ¼" CLEARANCE BETWEEN THEIR BOTTOM EDGE AND THE WORK SURFACE.

DESCRIPTION: CONCRETE SLAB GRABBER

PART #: 15500

WEIGHT: 22 LBS

C-SLAB GRABBERS ARE SUITABLE FOR THE FOLLOWING APPLICATIONS:



FALL PREVENTION:

C-Slab Grabber Guardrail Systems may be used in Fall Prevention applications ONLY.

- Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge and may be used in substitute of Fall Protection or safety netting systems.
- Installation requirements for C-Slab Grabber Guardrail Systems set forth in equipment instructions MUST be adhered to.
- Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.