




Model 5680 Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER Available with FaST™ Foam Scrubbing Technology

Feature			
Scrubbing System			
Cleaning path (3 paths available)	28-inch/700 mm	32-inch/800 mm	36-inch/900 mm
Solution tank capacity	30 gallon/114 liter		
Solution flow rates			
Conventional	0-1.5 gpm/0-5.7 lpm		
FaST™ Foam Scrubbing Technology	0.22 gpm/0.83 lpm		
Scrub head types	Disk or cylindrical		
Scrub head motors (all paths / types)	(2) 0.75 hp/ 0.5 kW		
Brush speed	200 rpm/750 rpm		
Disk/cylindrical			
Brush down pressure			
Disk (2-position)	100 & 200 lb/45.5 & 91 kg		
Cylindrical (1-position)	85 lb/39 kg		
Brush/pad driver quantity & dimensions			
Disk (D)	(2) 14-inch/355 mm	(2) 16-inch/405 mm	(2) 18-inch/455 mm
Cylindrical (L x D)	(2) 28 x 6-inch/ 700 x 150 mm	(2) 32x 6-inch/ 800 x 150 mm	(2) 36 x 6-inch/ 900 x 150 mm
Recovery System			
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)		
Vacuum fan			
Motor	0.8 hp/0.6 KW		
Stages	3-stage		
Water lift	73-inch/1,855 mm		
Propelling System			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36V system, charger included)			
Standard	(6) 6V, 235 AH		
Optional	(6) 6V, 335 AH		
Gradeability (Ramp climb)			
Full	6.0°		
Empty	8.0°		
Machine Dimensions / Sound level			
Length	63-inch/1,600 mm		
Width			
Body	28.25-inch/720mm	28.25-inch/720mm	28.25-inch/720mm
Scrub head	30-inch/760 mm	34-inch/865 mm	38-inch/965 mm
Squeegee	37.5-inch/955 mm	42-inch/1,065 mm	45.5-inch/1,155mm
Height	43-inch/1,090 mm		
Net weight			
Less batteries	403 lb/183 kg		
With 235 AH batteries	805 lb/366 kg		
With 335 AH batteries	985 lb/448 kg		
Minimum aisle turn	66.25-inch/1,680 mm	67-inch/1,700 mm	67.5-inch/1,725 mm
Sound level (operator's ear)	75 dBa		
Warranty		Please refer to your local Tennant representative for information.	



5680 ec-H2O™ Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER
with ec-H2O™ converted water scrubbing technology

Feature			
Scrubbing System			
Cleaning path (3 paths available)	28-inch/700 mm	32-inch/800 mm	36-inch/900 mm
Solution tank capacity	30 gallon/114 liter		
Solution flow rates: Disk Standard: Cylindrical Standard & Disk Optional Optional (Cylindrical & Disk) Conventional Mode Option	.22 gpm/0.83 lpm .33 gpm / 1.25 lpm & .44 gpm / 1.66 lpm 0–1.5 gpm / 0-5.7 lpm		.30 gpm / 1.1 lpm .44 gpm / 1.66 lpm & .53 gpm/ 2.0 lpm 0–1.5 gpm / 0-5.7 lpm
Scrub head types Scrub head motors (all paths / types) Brush speed Disk/cylindrical Brush down pressure Disk (2-position) Cylindrical (1-position)	Disk or cylindrical (2) 0.75 hp/ 0.5 kW 200 rpm/750 rpm 100 & 200 lb/45.5 & 91 kg 85 lb/39 kg		
Brush/pad driver quantity & dimensions Disk (D) Cylindrical (L x D)	(2) 14-inch/355 mm (2) 28 x 6-inch/ 700 x 150 mm	(2) 16-inch/405 mm (2) 32x 6-inch/ 800 x 150 mm	(2) 18-inch/455 mm (2) 36 x 6-inch/ 900 x 150 mm
Environmental Impact (Annually) *			
Chemical use reduction Packaging reduction Water use reduction	183 gallons 111 lbs 8190 gallons		
Recovery System			
Recovery tank capacity	40 gallon/151 liter (Includes demisting chamber)		
Vacuum fan Motor Stages Water lift	0.8 hp/0.6 KW 3-stage 73-inch/1,855 mm		
Propelling System			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36V system, charger included) Standard Optional	(6) 6V, 235 AH (6) 6V, 335 AH		
Gradeability (Ramp climb) Full Empty	6.0° 8.0°		



5680 ec-H2O™ Specifications

BATTERY-POWERED WALK-BEHIND SCRUBBER with ec-H2O™ converted water scrubbing technology

Machine Dimensions / Sound level			
Length	63-inch/1,600 mm		
Width			
Body	28.25-inch/720mm	28.25-inch/720mm	28.25-inch/720mm
Scrub head	30-inch/760 mm	34-inch/865 mm	38-inch/965 mm
Squeegee	37.5-inch/955 mm	42-inch/1,065 mm	45.5-inch/1,155mm
Height	43-inch/1,090 mm		
Net weight			
Less batteries	403 lb/183 kg		
With 235 AH batteries	805 lb/366 kg		
With 335 AH batteries	985 lb/448 kg		
Minimum aisle turn	66.25-inch/1,680 mm	67-inch/1,700 mm	67.5-inch/1,725 mm
Sound level (operator's ear)	75 dBA		
Warranty	Please refer to your local Tennant representative for information.		

* Estimates based on requiring, at minimum, 1.5 tanks to clean the facility / area per day. 2 oz of chemical per gallon of water and scrubbing 5 times per week or 260 times per year.

ec-H2O is certified to provide high traction by the National Floor & Safety Institute

