

Distributed By:

**One Source**  
RENTALS • SALES • SERVICE

[www.onesourcerental.com](http://www.onesourcerental.com)



Wheel kit fits 84-inch sweeper only – keeps the cutting edge off the ground to lengthen life, but can be compressed if needed to scrape material or sweep in reverse.

## Sweeper

Now you can sweep, collect and dump dirt and other debris with just one attachment. Ideal for construction, industrial or municipal jobs, the hydraulically driven Bobcat sweeper is easy to attach and simple to operate going either forward or reverse. It's perfect for cleaning parking lots, sidewalks, docks, warehouses and more.

The sweeper's floating bristle head follows surface contours independent of the bucket, providing improved surface contact on slopes for better sweeping consistency. The floating head also offers ideal down-pressure for longer bristle life, reducing the number of required bristle adjustments.

### Sweeper Features:

- Reversible cutting edge helps cut through caked-on mud.
- Polypropylene bristles deposit dirt and other debris in the bucket, which can be dumped when full.\*
- Use the sweeper to spread material evenly across a site.
- Six sizes to fit a variety of Bobcat machines.

## Specifications Sweeper

	44 in.	48 in.	54 in.	60 in.	72 in.	84 in.
Sweep Width	44 in. (1118 mm)	48 in. (1219 mm)	54 in. (1372 mm)	60 in. (1524 mm)	72 in. (1829 mm)	84 in. (2134 mm)
Overall Width	48.3 in. (1227 mm)	52.3 in. (1328 mm)	58.3 in. (1481 mm)	66.2 in. (1681 mm)	78.2 in. (1986 mm)	89.9 in. (2284 mm)
Weight	555 lb. (252 kg)	595 lb. (270 kg)	650 lb. (295 kg)	758 lb. (344 kg)	845 lb. (383 kg)	975 lb. (442 kg)
Bucket Capacity, Heaped	6.6 cu. ft. (0.19 m <sup>3</sup> )	7.3 cu. ft. (0.21 m <sup>3</sup> )	8.2 cu. ft. (0.23 m <sup>3</sup> )	12.0 cu. ft. (0.34 m <sup>3</sup> )	14.4 cu. ft. (0.41 m <sup>3</sup> )	18.5 cu. ft. (0.52 m <sup>3</sup> )
Bucket Capacity, Swept	5.3 cu. ft. (0.15 m <sup>3</sup> )	5.8 cu. ft. (0.16 m <sup>3</sup> )	6.6 cu. ft. (0.19 m <sup>3</sup> )	8.6 cu. ft. (0.24 m <sup>3</sup> )	10.4 cu. ft. (0.29 m <sup>3</sup> )	11.8 cu. ft. (0.33 m <sup>3</sup> )
Broom Diameter	21.4 in. (544 mm)	21.4 in. (544 mm)	21.4 in. (544 mm)	21.4 in. (544 mm)	21.4 in. (544 mm)	24 in. (610 mm)


Bristle Material Replaceable polypropylene sections (steel sections available)

Cutting Edge Replaceable steel


Broom rpm @ 15 gpm 185 185 185 217 217 215

Wheel Kit N/A N/A N/A N/A N/A Optional

Gutter Brush N/A N/A N/A Optional Optional Optional



SWEEPS & COLLECTS TRAVELING FORWARD



SWEEPS & COLLECTS TRAVELING IN REVERSE



DUMPS/SPREADS MATERIAL

### Gutter Brush Dimensions:

Approved sweeper models: 60, 72 in. 84 in.

Brush diameter:	24 in.	24 in.
Reach in front of sweeper:	26 in.	35 in.
Reach to the side of sweeper:	14 in.	7.6 in.
Height in sweeping position:	22 in.	19 in.
Height in storage position:	51 in.	43 in.

Only one gutter brush can be installed per sweeper.



### APPROVED AND NON-APPROVED LOADER-SWEeper COMBINATIONS

	APPROVED	LIFT RESTRICTIONS*	NON-APPROVED
SWEEPER MODEL	500 lb. (227 kg)	550 lb. (249 kg)	700 lb. (318 kg)
44 in.	Red	Red	Red
48 in.	Red	Red	Red
54 in.	Red	Red	Green

SWEEPER MODEL	1250 lb. (568 kg)	1500 lb. (680 kg)	1750 lb. (794 kg)	1900 lb. (864 kg)	2200 lb. (1000 kg)	2500 lb. (1140 kg)	3300 lb. (1497 kg)
60 in.	Grey	Red	Red	Red	Red	Red	Red
72 in.	Red	Red	Red	Red	Red	Green	Red
84 in.	Red	Red	Red	Red	Red	Green	Green

\*Lift restriction requires that loaded sweeper not be lifted more than 1 foot (0.3 m). Tipping can result.