

# INTUITIVE USABILITY, OUTSTANDING COLOR QUALITY, HIGH PRODUCTIVITY

The imageRUNNER ADVANCE C5500 Series is designed to improve office productivity and to deliver high-quality color output for demanding office environments. These intelligent systems provide an intuitive user experience and support Canon's holistic business solutions.

Print up to 60 ppm in color/black and white  
Scan up to 160 ipm (300 dpi) (BW, color, duplex)  
Print up to 12" x 18"  
6,350-sheet maximum paper capacity



## Workflow Efficiency

- An intuitive user interface with a large, responsive color touch-screen with smartphone-like usability helps make carrying out tasks easy.
- My ADVANCE enables a unique, personal experience, creating a customized user experience tailored to meet each user's workflow needs.
- Canon's MEAP platform supports a range of integrated solutions designed to simplify workflow and achieve a holistic business solution.
- Scalable support for mobile and flexible work styles can help increase efficiency by allowing workers to capture or print documents and access certain cloud applications.<sup>1</sup>
- Scan and convert documents to Searchable PDF, Microsoft® Word, and Microsoft® PowerPoint® files through a single-pass, duplexing document feeder that holds up to 150 originals.
- Intelligent features, such as motion sensor technology to wake the device from sleep mode and the ability to remove blank pages when scanning, help maximize productivity.

## Security

- Control who has access to the device with authentication by using the standard Universal Login Manager application.
- Help limit unauthorized distribution of sensitive information with an array of standard and optional document security features.
- Help facilitate information privacy and security by controlling access with IPsec, port filtering capabilities, and SSL technology.

## Cost Management



- The ability to apply print policies, monitor output, and restrict usage by user can help reduce unnecessary printing, enable cost recovery, and help save money on paper and toner.
- Tight integration with output management solutions, such as optional uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, contribute to maximizing uptime and can help reduce time spent by IT resolving issues.
- Consistent user operation, combined with remote and centralized fleet management, can help simplify IT management of a single device or fleet.



## Device and Fleet Management

- The ability to pre-configure devices makes installation easy, and fleet management is simplified with the ability to synchronize settings across multiple devices.
- Canon's device management tools give you a centralized point of control across your entire fleet, including the ability to check device status and consumables, turn off devices remotely, capture meter readings, as well as manage address books and printer drivers.
- Standard Genuine Adobe® PostScript® and PCL® support integration with enterprise applications and legacy systems to help streamline business processes.

## Configuration



## Quality and Reliability

- Canon's signature reliability and engine technologies contribute to high-quality output to help meet the needs of busy departments.
- Outstanding imaging technologies and toner allow for consistently striking images using Canon's V<sup>2</sup> color profile and 1200-dpi print resolution.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished, intuitive user maintenance videos, the ability to replace toner on the fly, and automatic job rerouting (with optional solutions).

## Sustainability

- Fusing technologies, CS toner, and innovative sleep mode features help lower overall energy consumption.
- Help minimize waste with default two-sided printing, Secure Print, and the ability to hold print jobs, preview them and change print settings at the device, so you can achieve the results you want the first time.
- ENERGY STAR® certified and rated EPEAT® Gold.<sup>2</sup>



## Main Unit

### Type

Color Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

### Processor Speed

Canon Dual Custom Processor (Shared)

### Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

### Memory

4.0 GB RAM

### Hard Disk

Standard: 250 GB/Maximum: 1 TB

### Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

Others  
Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)  
Optional: Serial Interface, Copy Control Interface

### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets  
Maximum: 3,450 Sheets  
(With External Finisher and Copy Tray)

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes,  
100-sheet Stack Bypass  
Optional: Dual 550-sheet Paper Cassettes  
(CASSETTE FEEDING UNIT-AMI),  
2,450-sheet High Capacity Paper  
Cassette (HIGH CAPACITY CASSETTE  
FEEDING UNIT-A1),  
2,700-sheet Paper Deck  
(PAPER DECK UNIT-F1)

### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets  
Maximum: 6,350 Sheets

### Finishing Capabilities

Standard: Collate, Group  
With Inner Finisher: Collate, Group, Offset, Staple, Hole Punch  
Finisher: Staple-free Staple, Staple On Demand  
With External Finishers: Collate, Group, Offset, Staple, Booklet, Hole Punch, Staple-free Staple, Staple On Demand

### Supported Media Types

Paper: Thin, Plain, Recycled, Color, Heavy,  
Cassettes (1/2): Pre-punched, Letterhead, Bond,  
Transparency, Tab, Envelope  
Stack Bypass: Thin, Plain, Recycled, Color, Heavy,  
Pre-punched, Labels, Letterhead, Bond,  
Coated, Transparency, Tab, Tracing,<sup>3</sup>  
Envelope

### CASSETTE FEEDING UNIT-AMI

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond, Transparency

### HIGH CAPACITY CASSETTE FEEDING UNIT-A1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond

### PAPER DECK UNIT-F1

Thin, Plain, Recycled, Color, Heavy, Pre-punched,  
Letterhead, Bond

### Supported Media Sizes

Paper: Letter, Executive, Statement-R, Envelope  
Cassette 1: [No.10 (COM10), DL, ISO-C5], Custom Size  
(3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Cassette 2: Executive, Statement-R, Envelope  
[No.10 (COM10), Monarch, DL, ISO-C5],  
Custom Size (3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Executive, Statement, Statement-R,  
Envelope [No.10 (COM10), Monarch, DL,  
ISO-C5], Envelope Custom Size (3-7/8" x  
3-7/8" to 12-5/8" x 18"), Custom Size  
(3-7/8" x 5-1/2" to 12-5/8" x 18"), Free  
Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

### CASSETTE FEEDING UNIT-AMI

12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive,  
Statement-R, Custom Size (3-7/8" x 7-1/8" to 12" x 18")

HIGH CAPACITY CASSETTE FEEDING UNIT-A1: Letter  
PAPER DECK UNIT-F1: Letter

### Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

### Warm-up Time

From Power On: 30 Seconds  
From Sleep Mode: 10 Seconds  
Quick Startup Mode: 4 Seconds<sup>4</sup>

### Dimensions (W x D x H)

24-3/8" x 29-1/4" x 47-2/7" (620 mm x 742 mm x 1201 mm)<sup>5</sup>

### Installation Space (W x D)

Basic: Stack Bypass + Cassette drawers open:  
37-1/8" x 46-3/8" (943 mm x 1176 mm)<sup>5</sup>

### Weight

Approx. 362.7 lb. (164.5 kg)<sup>6</sup>

## Print Specifications

### Print Speed (BW and Color)

iR ADV Up to 60 ppm (Letter); Up to 36 ppm  
C5560i: (Letter-R); Up to 34 ppm (Legal);  
Up to 32 ppm (11" x 17")  
iR ADV Up to 50 ppm (Letter); Up to 30 ppm  
C5550i: (Letter-R); Up to 29 ppm (Legal);  
Up to 27 ppm (11" x 17")  
iR ADV Up to 40 ppm (Letter); Up to 24 ppm  
C5540i: (Letter-R); Up to 23 ppm (Legal);  
Up to 22 ppm (11" x 17")  
iR ADV Up to 35 ppm (Letter); Up to 23 ppm  
C5535i: (Letter-R); Up to 21 ppm (Legal);  
Up to 18 ppm (11" x 17")

### Print Resolution

1200 dpi x 1200 dpi, 600 dpi x 600 dpi

### Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

### Direct Print

Available from USB, Advanced Box, Remote UI, and  
Web Access<sup>7</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>8</sup> XPS

### Printing from Mobile and Cloud-based Services

A range of software and MEAP-based solutions are  
available to provide printing from compatible mobile  
devices or Internet-connected devices and cloud-based  
services depending on your requirements. Please contact  
your sales representative for further information.<sup>9</sup>

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT J/K/S/T (Japanese,  
Korean, Simplified and Traditional  
Chinese),<sup>10</sup> Barcode Fonts<sup>11</sup>

PS fonts: 136 Roman

### Operating System<sup>12</sup>

UFR II: Server 2003/Server 2003 R2/Windows  
Vista/Server 2008/Windows 7/Server  
2008 R2/Windows 8/Server 2012/  
Windows 8.1/Server 2012 R2/Windows 10,  
MAC OS X (10.6.8 or later)  
PCL: Server 2003/Server 2003 R2/Windows  
Vista/Server 2008/Windows 7/Server  
2008 R2/Windows 8/Server 2012/  
Windows 8.1/Server 2012 R2/Windows 10  
PS: Server 2003/Server 2003 R2/Windows  
Vista/Server 2008/Windows 7/Server  
2008 R2/Windows 8/Server 2012/  
Windows 8.1/Server 2012 R2/Windows 10,  
MAC OS X (10.6.8 or later)

## Copy Specifications

### Copy Speed (BW and Color)

iR ADV Up to 60 ppm (Letter); Up to 36 ppm  
C5560i: (Letter-R); Up to 34 ppm (Legal);  
Up to 32 ppm (11" x 17")  
iR ADV Up to 50 ppm (Letter); Up to 30 ppm  
C5550i: (Letter-R); Up to 29 ppm (Legal);  
Up to 27 ppm (11" x 17")  
iR ADV Up to 40 ppm (Letter); Up to 24 ppm  
C5540i: (Letter-R); Up to 23 ppm (Legal);  
Up to 22 ppm (11" x 17")  
iR ADV Up to 35 ppm (Letter); Up to 23 ppm  
C5535i: (Letter-R); Up to 21 ppm (Legal);  
Up to 18 ppm (11" x 17")

### First-Copy-Out Time

iR ADV As fast as 2.9 seconds (BW)/  
C5560i: 4.5 seconds (Color)  
iR ADV As fast as 3.5 seconds (BW)/  
C5550i: 5.2 seconds (Color)  
iR ADV As fast as 4.1 seconds (BW)/  
C5540i: 6.1 seconds (Color)  
iR ADV As fast as 4.9 seconds (BW)/  
C5535i: 7.4 seconds (Color)

### Copy Resolution

Reading: 600 dpi x 600 dpi  
Printing: 1200 dpi x 1200 dpi

### Multiple Copies

Up to 9,999 copies

### Magnification

25%–400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 73%, 78%

### Preset Enlargements

121%, 129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper  
Setting, Previous Settings, Favorite Settings, Finishing,  
Two-Sided, Density Adjustment, Original Type Selection,  
Interrupt Mode, Setting Confirmation/Cancel

### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing,  
Booklet, Job Build, N on 1, Add Cover, Insert Sheets,  
Different Size Originals, Density Adjustment, Original  
Type Selection, Transparency Cover Sheets, Page  
Numbering, Copy Set Numbering, Sharpness, Erase  
Frame, Secure Watermark, Print Date, Shift, Gutter,  
Print & Check, Negative/Positive, Repeat Images, Merge  
Job Blocks, Job Done Notice, Mirror Image, Print on Tab,  
Store in Mail Box, Superimpose Image, Copy ID Card,  
Detect Feeder Multi Sheet Feed, Free Size Original, Color  
Balance, Adjust One-Touch Color, Area Designation

## Scan Specifications

### Type

Color Platen and Single-Pass Duplexing Automatic  
Document Feeder

### Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m<sup>2</sup>)

### Color

Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]

### Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported Windows Vista/7/8/8.1/10 Windows  
OS: Server 2003/Server 2003 R2/Server  
2008/Server 2008 R2/Server 2012/  
Server 2012 R2

### Scan Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi,  
200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning  
to compatible mobile devices and certain cloud-based  
services depending on your requirements.

### Scan Speed (Letter)

Single-sided Scanning (BW):  
80 ipm (300 dpi)/80 ipm (600 dpi)  
Single-sided Scanning (Color):  
80 ipm (300 dpi)/60 ipm (600 dpi)  
Double-sided Scanning (BW):  
160 ipm (300 dpi)/150 ipm (600 dpi)  
Double-sided Scanning (Color):  
160 ipm (300 dpi)/80 ipm (600 dpi)

## Send Specifications

### Destination

E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV,  
Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

## Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

## Send Resolution

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

## Communication Protocol

File: FTP, SMB, WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

## File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word)

Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)

## Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Direct Send, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

## Fax Specifications (Optional)

### Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

### Compression Method

MH, MR, MMR,JBIG

### Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

### Sending/Recording Size

Statement-R to 11" x 17"

### Fax Memory

Up to 30,000 pages

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 dials

### Sequential Broadcast

Max. 256 addresses

### Memory Backup

Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

## Store Specifications

### Mail Box (Number Supported):

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box:

Communication Protocol: SMB or WebDAV

#### Supported

Client PC: Windows (Windows Vista/7/8/8.1/10)

#### Concurrent Connections (Max.):

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space:

Approx. 16 GB (Standard HDD)

Approx. 480 GB (Optional 1 TB HDD)

### Advanced Box Features:

Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support

## Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated)

Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP

### Document

Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration

Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan locking

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86° F

Humidity: 20 to 80% RH (no condensation)

## Power Requirements

C5560i/C5550i: 120-127V AC 60 Hz, 11.5 A

C5540i/C5535i: 120-127V AC, 60 Hz, 10 A

### Plug (Main Unit)

C5560i/C5550i: NEMA 5-20P

C5540i/C5535i: NEMA 5-15P

### Power Consumption

Maximum: Approx. 1.8 kWh

Standby: Approx. 66.2 W

Sleep Mode: Approx. 0.8 W<sup>13</sup>

Typical Electricity Consumption (TEC) Rating:

3.2 kWh (iR ADV C5560i)

2.0 kWh (iR ADV C5540i)

2.5 kWh (iR ADV C5550i)

1.6 kWh (iR ADV C5535i)

### Standards

ENERGY STAR® Certified

Rated EPEAT® Gold<sup>2</sup>

RoHS Compliant

## Consumables

### Toner

GPR-55 Toner<sup>14</sup>

### Toner Yield (Estimated @ 5% Coverage)

Black: 69,000 Images

Color (C,M,Y):<sup>14</sup> 60,000 Images

## Footnotes

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

<sup>2</sup> For current EPEAT rating (Gold/Silver/Bronze), please visit [www.epeat.net](http://www.epeat.net).

<sup>3</sup> Some types of tracing paper cannot be used.

<sup>4</sup> Time from device power-on to when copy jobs can be programmed.

<sup>5</sup> Includes main unit and either Cassette Feeding Unit-AMI, High Capacity Cassette Feeding Unit-AL, or Cabinet Type-N.

<sup>6</sup> Includes main unit, consumables, and Cassette Feeding Unit-AMI.

<sup>7</sup> PDF print from Web sites is supported.

<sup>8</sup> EPS can be printed directly only from the Remote User Interface.

<sup>9</sup> For more information, including compatibility, please visit <https://www.usa.canon.com/mobile-app>.

<sup>10</sup> Requires the optional PCL International Font Set-AL.

<sup>11</sup> Requires the optional Barcode Printer Kit-D1.

<sup>12</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>13</sup> 0.8 W Sleep mode not available in all circumstances due to certain settings.

<sup>14</sup> GPR-55L Toner also available for Color (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

For detailed specifications and a comprehensive list of optional accessories, see the imageRUNNER ADVANCE C5500 Series Specifications document.

For more information, call or visit  
1.800.815.4000 CSA.CANON.COM



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Adobe® and PostScript® 3™ are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft® and PowerPoint® are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. PCL® is a registered trademark of Hewlett-Packard Company. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Products shown with optional accessories. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21 or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2017 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

CSA/7-16-262

0817R3-CSA1RA5500SRSB-PDF-IH

